



48038989



**SCHUKO socket outlet with 2 x USB with enhanced touch protection, Berker S.1/B.3/B.7, polar white glossy**

Technical features

**Architecture**

Fixing mode flush-mounting

**Connectivity**

Type of USB port AA  
- with 2 USB sockets type A

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V
Efficiency at low load (10 %)	76,1 %
Average active efficiency	84,7 %
Frequency	50 Hz
Rated current	16 A

**Voltage**

Input voltage	220...250 V AC
Output voltage	4,75...5,25 V DC

**Electric current**

Input current	max. 500 mA
Output current	2,4 A
Output current when operating both sockets	max. 2400 mA
Output current per socket	max. 2400 mA
Rated current	16 A

**Fuse**

Fuse short-circuit and overload proof (electronic fuse)

**Power**

Power consumption (standby)	< 50 mW
Output power	12 W
No-load power consumption	68 mW

**Cover, door**

Cover Central cover plate

**Materials**

Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Surface appearance	glossy

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

### Connection

Conductor cross-section (flexible)	1,5...2,5 mm <sup>2</sup>
------------------------------------	---------------------------

Conductor cross-section (rigid)	1,5...2,5 mm <sup>2</sup>
---------------------------------	---------------------------

- with plug-in terminals

### Equipment

With transparent product label holder	no
---------------------------------------	----

### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

### Safety

IK protection code against mechanical impacts	02
---	----

Protection index IP	IP20
---------------------	------

Enhanced contact protection	according to VDE 0620-1:2021-02
-----------------------------	---------------------------------

### Use conditions

Operating temperature	5...35 °C
-----------------------	-----------

### Identification

Main design line	Berker S.1/B.3/B.7
------------------	--------------------

Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
--------------------------	------------------------------------