



16512049



Rocker for accessible construction with tactile symbol for light, with clear lens, Berker R.1/R.3/R.8, polar white glossy

Technical features

Controls and indicators

- also for KNX applications: push-button, 1 gang
- for illuminated rocker push-buttons

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Settings

Shading parameter	R1_bialy
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck
- for lighting and monitoring circuit	

Use cases

Barrier-free building	based on DIN 18040
-----------------------	--------------------

Use

Differentiation characteristic 1 - Sales	with tactile symbol for light
Differentiation characteristic 2 - Sales	with clear lens

Identification

Application, usage	Flush-mounted wet-room installation, Light control
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

Instructions

- The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.