



16512089



**Rocker for accessible construction with tactile symbol for bell, with clear lens, Berker R.1/R.3/R.8, polar white glossy**

Technical features

**Controls and indicators**

- also for KNX applications: push-button, 1 gang
- for illuminated rocker push-buttons

**Materials**

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

**Installation, mounting**

Installation mode	clamp fastening
-------------------	-----------------

**Settings**

Shading parameter	R1_bialy
Laser parameter	R1_weiß

**Equipment**

Type of configuration	Laserdruck
-----------------------	------------

**Use cases**

Barrier-free building	based on DIN 18040
-----------------------	--------------------

**Use**

Differentiation characteristic 1 - Sales	with tactile symbol for bell
Differentiation characteristic 2 - Sales	with clear lens

**Identification**

Application, usage	Light control, Flush-mounted wet-room installation
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

**Instructions**

- The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.