Rocker for accessible construction with guide for mouth-held rod, with clear lens, Berker R.1/R.3/R.8, polar white glossy

16612049

Technical features

Controls and indicators

- also for KNX applications: push-button, 1gang, and group push-button, 1gang
- for change-over/intermediate switch
- for rocker push-buttons

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

Installation, mounting

Installation mode	clamp fastening

Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck

- for lighting and monitoring circuit

Use cases

Barrier-free building	based on DIN 18040

Use

Differentiation characteristic 1 - Sales	with guide for mouth-held rod
Differentiation characteristic 2 - Sales	with clear lens

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

Instructions

- The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.