


2909



Rotary dimmer (R, LED) with soft-lock, Light control, others

Technical features

Main electrical features

Nominal voltage	230 V
Frequency	50 Hz

Voltage

Operating voltage	230 V AC
-------------------	----------

Fuse

Fine-wire fuse	T 0,8 H 250
Fuse	short-circuit and overload proof (fine-wire fuse)

Power

Power consumption (standby)	≈ 0,2 W
-----------------------------	---------

Materials

Colour	not applicable
Material	Plastic/metal

Dimensions

Insertion depth	31 mm
Axis dimension Ø	4 mm

LED control

Dimmable 230 V retrofit LED lamps	3...40 W
-----------------------------------	----------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...200 W
--	------------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Type of load	universal
Conductor cross-section	max. 1 x 0,5...2,5 mm ²

Equipment

- phase cut-on

Use

Differentiation characteristic 3 - Sales	with soft-lock
--	----------------

Safety

Halogen free	yes
--------------	-----

temperatur

Ambient temperature	-5...45 °C
---------------------	------------

Identification

Application, usage	Light control
Main design line	Light control
Secondary design line(s)	Light control, House electronics
