



294410



ε



Universal rotary dimmer with centre plate (R, L, C, LED) with soft-lock, Serie 1930/Glas, polar white glossy

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage	230 V
Frequency	50/60 Hz

Voltage

Operating voltage	230 V AC
- voltage test possible without dismantling	

Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

Power

Dimmable conventional transformers	20...420 VA
Loss power at full load	≈ 4 W
Electronic transformers	20...420 W

Measurement

Extension unit input	with input for extension units insert for universal rotary dimmer, with extension unit input for push-button (NO contact) with single-surface operation
----------------------	---

Materials

Colour of design line	polar white
Colour	polarwhite
Material	Plastic/metal

Dimensions

Insertion depth	24 mm
Axis dimension Ø	4 mm

LED control

Dimmable 230 V retrofit LED lamps	3...100 W
-----------------------------------	-----------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...420 W
--	------------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Type of load	Universal and LED Retrofit
Conductor cross-section	0,5...4 mm ²
- with screw terminals	

Scope of delivery

- with incremental encoder
-

Equipment

- phase cut-on, cut-off or LED phase cut-on according to load type, self-learning
 - with brightness memory
-

Use

Differentiation characteristic 3 - Sales	with soft-lock
--	----------------

Identification

Application, usage	Light control
Main design line	Serie 1930/Glas
Secondary design line(s)	Serie 1930, Serie Glass
