


2973



## Universal rotary dimmer (R, L, C, LED) with soft-lock, Light control

### Technical features

### Functions

- bulb-preserving soft startup

### Controls and indicators

- with soft-lock

### Main electrical features

Nominal voltage	230 V
Frequency	50/60 Hz

### Voltage

Operating voltage	230 V AC
- voltage test possible without dismantling	

### Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

### Power

Dimmable conventional transformers	20...210 VA
Loss power at full load	≈ 2 W
Electronic transformers	20...210 W

### Materials

Colour	not applicable
Material	Plastic/metal

### Dimensions

Insertion depth	24 mm
Axis dimension Ø	4 mm

### LED control

Dimmable 230 V retrofit LED lamps	3...60 W
-----------------------------------	----------

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...210 W
--	------------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Type of load	Universal and LED Retrofit
Conductor cross-section	0,5...4 mm <sup>2</sup>
- with screw terminals	

**Scope of delivery**

- with incremental encoder

**Equipment**

- phase cut-on or cut-off according to load type, self-learning
- with brightness memory

**Use**

Differentiation characteristic 3 - Sales with soft-lock

**Identification**

Application, usage Light control

Main design line Light control