


85121200



IP20

## Relay insert Electronics platform

### Technical features

### Main electrical features

Frequency	50/60 Hz
-----------	----------

### Voltage

Operating voltage	230 V AC
-------------------	----------

### Power

Dimmable conventional transformers	1500 VA
------------------------------------	---------

Power consumption, standby (Channel 1/Channel 2)	< 0.3/0.7 W
--	-------------

Power consumption (standby)	< 0,3 W
-----------------------------	---------

Minimum contact load	≈ 15 W
----------------------	--------

Electronic transformers and dual-mode transformers	1500 W
--	--------

### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

Extension unit input	with extension unit input for push-button (NO contact), single-surface operation and motion detector extension unit
----------------------	---

### Materials

Colour	not applicable
--------	----------------

Material	Plastic/metal
----------	---------------

- no conductive connection between supporting ring and spreading claws

### Dimensions

Insertion depth	32 mm
-----------------	-------

Claw guidance installation depth	32 mm
----------------------------------	-------

Housing installation depth	22 mm
----------------------------	-------

### Lighting control

Fluorescent lamps with electrical ballast (EB)	1000 W
--	--------

- uncompensated	1100 VA
-----------------	---------

### Fluorescent bulbs control

Dimmable energy-saving lamps	440 W
------------------------------	-------

Compact fluorescent lamps with electronic ballast	22 x 20 W
---	-----------

Fluorescent lamps in duo circuit	1000 W
----------------------------------	--------

Fluorescent lamps parallel compensated	1000 W /130 μF
--	----------------

### LED control

230 V retrofit LED lamps	440 W
--------------------------	-------

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	2300 W
--	--------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Screw terminals (max.)	2 x 1,5/1 x 2,5 mm <sup>2</sup>
------------------------	---------------------------------

Number of substations	unlimited
-----------------------	-----------

- with screw terminals

### Cable

Load cable length	max. 100 m
-------------------	------------

Cable length, extensions	max. 50 m
--------------------------	-----------

### Equipment

- also usable as push-button relay switch

### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

- low intrinsic energy requirement

### Identification

Application, usage	Motion detector, KNX radio- operating systems, Light control
--------------------	---

Main design line	Electronics platform
------------------	----------------------