

# Product data sheet

## Satellite insert 3-wire, power supply



### Reference number

1723 NE

### Satellite insert 3-wire, power supply

for covers JUNG HOME ref.-no.: BT .. 17101 .., BT .. 17102 .., BT .. 17181 .., BT .. 17182 .., BT .. 1791 ..

for covers eNet ref.-no.: FM .. 1700 .., FM .. 1701 ..

for covers LB Management ref.-no.: .. 1700 .., .. 1702 .., .. 1750 D .., .. 17180 .., .. 17280 ..

for covers KNX RF ref.-no.: .. 10911 ST RF .., .. 10921 ST RF ..

### Intended use

- Extension unit operation of suitable inserts
- Satellite for extending the detection field of motion and presence detectors
- Central control of multiple main devices
- Operation with suitable cover
- Installation in flush box with dimensions according to DIN 49073
- Neutral conductor required

### Technical data

Rated voltage:	AC 230 V ~
Mains frequency:	50/60 Hz
Ambient temperature:	-20 ... +45 °C
Connection	screw terminals
single wire:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded without ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded with ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 1.5 mm <sup>2</sup>
Total length of extension unit cable:	max. 100 m