

# Product data sheet

## LB Management room thermostat set



### Reference number

TR D LS 1790 SW

### LB Management room thermostat set

consists of room thermostat insert (ref.-no.: 1790 RTR) and display (ref.-no.: .. 1790 D ..)

### Technical data

Rated voltage:	AC 230 V ~
Mains frequency:	50/60 Hz
Stand-by power depending on the cover:	approx. 0.1 ... 0.5 W
Switching current 230 V AC1:	10 mA ... 16 A
Connected load:	max. 3,600 W
Connection	
single wire:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded without ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded with ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 1.5 mm <sup>2</sup>
Ambient temperature:	-5 ... +45 °C
Accuracy per month:	± 10 s
Power reserve:	> 4 h
Regulator class (EU 811/2013):	nicht relevant
Contribution to energy efficiency:	2 %

### Colour:

black

### Range:

LS range

### Material:

Glass

### Material:

glass